
django-downloadview Documentation

Release 1.6

Benoît Bryon

March 03, 2014

django-downloadview makes it easy to serve files with Django:

- you manage files with Django (permissions, search, generation, ...);
- files are stored somewhere or generated somehow (local filesystem, remote storage, memory...);
- django-downloadview helps you stream the files with very little code;
- django-downloadview helps you improve performances with reverse proxies, via mechanisms such as Nginx's X-Accel.

Example

Let's serve a file stored in a `FileField` of some model:

```
from django.conf.urls import url, url_patterns
from django_downloadview import ObjectDownloadView
from demoproject.download.models import Document  # A model with a FileField

# ObjectDownloadView inherits from django.views.generic.BaseDetailView.
download = ObjectDownloadView.as_view(model=Document, file_field='file')

url_patterns = (
    url('^download/(?P<slug>[A-Za-z0-9_-]+)/$', download, name='download'),
)
```

Ressources

- Documentation: <http://django-downloadview.readthedocs.org>
- PyPI page: <http://pypi.python.org/pypi/django-downloadview>
- Code repository: <https://github.com/benoitbryon/django-downloadview>
- Bugtracker: <https://github.com/benoitbryon/django-downloadview/issues>
- Continuous integration: <https://travis-ci.org/benoitbryon/django-downloadview>
- Roadmap: <https://github.com/benoitbryon/django-downloadview/issues/milestones>

3.1 Overview, concepts

Given:

- you manage files with Django (permissions, search, generation, ...)
- files are stored somewhere or generated somehow (local filesystem, remote storage, memory...)

As a developer, you want to serve files quick and efficiently.

Here is an overview of `django-downloadview`'s answer...

3.1.1 Generic views cover commons patterns

Choose the generic view depending on the file you want to serve:

- *ObjectDownloadView*: file field in a model;
- *StorageDownloadView*: file in a storage;
- *PathDownloadView*: absolute filename on local filesystem;
- *HTTPDownloadView*: URL (the resource is proxied);
- *VirtualDownloadView*: bytes, text, `StringIO`, generated file...

3.1.2 Generic views and mixins allow easy customization

If your use case is a bit specific, you can easily extend the views above or *create your own based on mixins*.

3.1.3 Views return `DownloadResponse`

Views return `DownloadResponse`. It is a special `django.http.StreamingHttpResponse` where content is encapsulated in a file wrapper.

Learn more in *Responses*.

3.1.4 DownloadResponse carry file wrapper

Views instantiate a *file wrapper* and use it to initialize responses.

File wrappers describe files: they carry files properties such as name, size, encoding...

File wrappers implement loading and iterating over file content. Whenever possible, file wrappers do not embed file data, in order to save memory.

Learn more about available file wrappers in *File wrappers*.

3.1.5 Middlewares convert DownloadResponse into ProxiedDownloadResponse

Before WSGI application use file wrapper to load file contents, middlewares (or decorators) are given the opportunity to capture `DownloadResponse` instances.

Let's take this opportunity to optimize file loading and streaming!

A good optimization it to delegate streaming to a reverse proxy, such as [nginx](http://nginx.org) ¹ via [X-Accel](http://wiki.nginx.org/X-accel) ² internal redirects.

`django_downloadview` provides middlewares that convert `DownloadResponse` into `ProxiedDownloadResponse`.

Learn more in *Optimize streaming*.

3.1.6 Testing matters

`django-downloadview` also helps you *test the views you customized*.

You may also write *healthchecks* to make sure everything goes fine in live environments.

3.1.7 What's next?

Let's install `django-downloadview`.

Notes & references

3.2 Install

Note: If you want to install a development environment, please see *Contributing*.

System requirements:

- Python version 2.7

Install the package with your favorite Python installer. As an example, with pip:

```
pip install django-downloadview
```

Installing `django-downloadview` will automatically trigger the installation of the following requirements:

¹ <http://nginx.org>

² <http://wiki.nginx.org/X-accel>

```
REQUIREMENTS = ['setuptools', 'Django>=1.5', 'requests', 'six']
```

Note: Since version 1.1, django-downloadview requires Django>=1.5, which provides `StreamingHttpResponse`.

Notes & references

See also:

- *Configure*
- *Changelog*
- *License*

3.3 Configure

Here is the list of settings used by *django-downloadview*.

3.3.1 INSTALLED_APPS

There is no need to register this application in your Django's `INSTALLED_APPS` setting.

3.3.2 MIDDLEWARE_CLASSES

If you plan to setup reverse-proxy optimizations, add `django_downloadview.SmartDownloadMiddleware` to `MIDDLEWARE_CLASSES`. It is a response middleware. Move it after middlewares that compute the response content such as `gzip` middleware.

Example:

```
MIDDLEWARE_CLASSES = [  
    'django.middleware.common.CommonMiddleware',  
    'django.contrib.sessions.middleware.SessionMiddleware',  
    'django.middleware.csrf.CsrfViewMiddleware',  
    'django.contrib.auth.middleware.AuthenticationMiddleware',  
    'django.contrib.messages.middleware.MessageMiddleware',  
    'django_downloadview.SmartDownloadMiddleware'  
]
```

3.3.3 DOWNLOADVIEW_BACKEND

This setting is used by `SmartDownloadMiddleware`. It is the import string of a callable (typically a class) of an optimization backend (typically a `BaseDownloadMiddleware` subclass).

Example:

```
DOWNLOADVIEW_BACKEND = 'django_downloadview.nginx.XAccelRedirectMiddleware'
```

See *Optimize streaming* for a list of available backends (middlewares).

When `django_downloadview.SmartDownloadMiddleware` is in your `MIDDLEWARE_CLASSES`, this setting must be explicitly configured (no default value). Else, you can ignore this setting.

3.3.4 DOWNLOADVIEW_RULES

This setting is used by `SmartDownloadMiddleware`. It is a list of positional arguments or keyword arguments that will be used to instantiate class mentioned as `DOWNLOADVIEW_BACKEND`.

Each item in the list can be either a list of positional arguments, or a dictionary of keyword arguments. One item cannot contain both positional and keyword arguments.

Here is an example containing one rule using keyword arguments:

```
DOWNLOADVIEW_RULES = [
    {
        'source_url': '/media/nginx/',
        'destination_url': '/nginx-optimized-by-middleware/',
    },
]
```

See *Optimize streaming* for details about builtin backends (middlewares) and their options.

When `django_downloadview.SmartDownloadMiddleware` is in your `MIDDLEWARE_CLASSES`, this setting must be explicitly configured (no default value). Else, you can ignore this setting.

3.4 Setup views

Setup views depending on your needs:

- *ObjectDownloadView* when you have a model with a file field;
- *StorageDownloadView* when you manage files in a storage;
- *PathDownloadView* when you have an absolute filename on local filesystem;
- *HTTPDownloadView* when you have an URL (the resource is proxied);
- *VirtualDownloadView* when you generate a file dynamically;
- *bases and mixins* to make your own.

3.4.1 ObjectDownloadView

`ObjectDownloadView` **serves files managed in models with file fields** such as `FileField` or `ImageField`.

Use this view like Django's builtin `DetailView`.

Additional options allow you to store file metadata (size, content-type, ...) in the model, as deserialized fields.

Simple example

Given a model with a `FileField`:

```
from django.db import models
```

```
class Document(models.Model):
    slug = models.SlugField()
    file = models.FileField(upload_to='object')
```

Setup a view to stream the file attribute:

```
from django_downloadview import ObjectDownloadView
```

```
from demoproject.object.models import Document
```

```
default_file_view = ObjectDownloadView.as_view(model=Document)
```

ObjectDownloadView inherits from BaseDetailView, i.e. it expects either slug or pk:

```
from django.conf.urls import patterns, url
```

```
from demoproject.object import views
```

```
urlpatterns = patterns(
    '',
    url(r'^default-file/(?P<slug>[a-zA-Z0-9_-]+)/$',
        views.default_file_view,
        name='default_file'),
)
```

Base options

ObjectDownloadView inherits from DownloadMixin, which has various options such as `basename` or `attachment`.

Serving specific file field

If your model holds several file fields, or if the file field name is not “file”, you can use `ObjectDownloadView.file_field` to specify the field to use.

Here is a model where there are two file fields:

```
from django.db import models
```

```
class Document(models.Model):
    slug = models.SlugField()
    file = models.FileField(upload_to='object')
    another_file = models.FileField(upload_to='object-other')
```

Then here is the code to serve “another_file” instead of the default “file”:

```
from django_downloadview import ObjectDownloadView
```

```
from demoproject.object.models import Document
```

```
another_file_view = ObjectDownloadView.as_view(  
    model=Document,  
    file_field='another_file')
```

Mapping file attributes to model's

Sometimes, you use Django model to store file's metadata. Some of this metadata can be used when you serve the file. As an example, let's consider the client-side basename lives in model and not in storage:

```
from django.db import models  
  
class Document(models.Model):  
    slug = models.SlugField()  
    file = models.FileField(upload_to='object')  
    basename = models.CharField(max_length=100)
```

Then you can configure the `ObjectDownloadView.basename_field` option:

```
from django_downloadview import ObjectDownloadView  
  
from demoproject.object.models import Document  
  
deserialized_basename_view = ObjectDownloadView.as_view(  
    model=Document,  
    basename_field='basename')
```

Note: `basename` could have been a model's property instead of a `CharField`.

See details below for a full list of options.

API reference

```
class django_downloadview.views.object.ObjectDownloadView(**kwargs)  
    Bases: django.views.generic.detail.SingleObjectMixin,  
           django_downloadview.views.base.BaseDownloadView
```

Serve file fields from models.

This class extends `SingleObjectMixin`, so you can use its arguments to target the instance to operate on: `slug`, `slug_kwarg`, `model`, `queryset`...

In addition to `SingleObjectMixin` arguments, you can set arguments related to the file to be downloaded:

- `file_field`;
- `basename_field`;
- `encoding_field`;
- `mime_type_field`;
- `charset_field`;
- `modification_time_field`;
- `size_field`.

`file_field` is the main one. Other arguments are provided for convenience, in case your model holds some (deserialized) metadata about the file, such as its basename, its modification time, its MIME type... These fields may be particularly handy if your file storage is not the local filesystem.

`file_field = 'file'`

Name of the model's attribute which contains the file to be streamed. Typically the name of a `FileField`.

`basename_field = None`

Optional name of the model's attribute which contains the basename.

`encoding_field = None`

Optional name of the model's attribute which contains the encoding.

`mime_type_field = None`

Optional name of the model's attribute which contains the MIME type.

`charset_field = None`

Optional name of the model's attribute which contains the charset.

`modification_time_field = None`

Optional name of the model's attribute which contains the modification

`size_field = None`

Optional name of the model's attribute which contains the size.

`get_file()`

Return `FieldFile` instance.

The file wrapper is model's field specified as `file_field`. It is typically a `FieldFile` or subclass.

Raises `FileNotFound` if instance's field is empty.

Additional attributes are set on the file wrapper if `encoding`, `mime_type`, `charset`, `modification_time` or `size` are configured.

`get_basename()`

Return client-side filename.

`get(request, *args, **kwargs)`

3.4.2 StorageDownloadView

`StorageDownloadView` serves files given a storage and a path.

Use this view when you manage files in a storage (which is a good practice), unrelated to a model.

Simple example

Given a storage:

```
from django.core.files.storage import FileSystemStorage
```

```
storage = FileSystemStorage()
```

Setup a view to stream files in storage:

```
from django_downloadview import StorageDownloadView
```

```
static_path = StorageDownloadView.as_view(storage=storage)
```

The view accepts a `path` argument you can setup either in `as_view` or via `URLconfs`:

```
from django.conf.urls import patterns, url

from demoproject.storage import views

urlpatterns = patterns(
    '',
    url(r'^static-path/(?P<path>[a-zA-Z0-9_-]+\.[a-zA-Z0-9]{1,4})$',
        views.static_path,
        name='static_path'),
)
```

Base options

`StorageDownloadView` inherits from `DownloadMixin`, which has various options such as `basename` or `attachment`.

Computing path dynamically

Override the `StorageDownloadView.get_path()` method to adapt path resolution to your needs.

As an example, here is the same view as above, but the path is converted to uppercase:

```
from django_downloadview import StorageDownloadView

class DynamicStorageDownloadView(StorageDownloadView):
    """Serve file of storage by path.upper()."""
    def get_path(self):
        """Return uppercase path."""
        return super(DynamicStorageDownloadView, self).get_path().upper()
```

```
dynamic_path = DynamicStorageDownloadView.as_view(storage=storage)
```

API reference

class `django_downloadview.views.storage.StorageDownloadView` (***kwargs*)

Bases: `django_downloadview.views.path.PathDownloadView`

Serve a file using storage and filename.

storage = `<django.core.files.storage.DefaultStorage object at 0x32a9f10>`

Storage the file to serve belongs to.

path = `None`

Path to the file to serve relative to storage.

get_path()

Return path of the file to serve, relative to storage.

Default implementation simply returns view's `path` attribute.

Override this method if you want custom implementation.

```
get_file()
```

Return StorageFile instance.

3.4.3 PathDownloadView

PathDownloadView **serves file given a path on local filesystem.**

Use this view whenever you just have a path, outside storage or model.

Warning: Take care of path validation, especially if you compute paths from user input: an attacker may be able to download files from arbitrary locations. In most cases, you should consider managing files in storages, because they implement default security mechanisms.

Simple example

Setup a view to stream files given path:

```
import os

from django_downloadview import PathDownloadView

# Let's initialize some fixtures.
app_dir = os.path.dirname(os.path.abspath(__file__))
project_dir = os.path.dirname(app_dir)
fixtures_dir = os.path.join(project_dir, 'fixtures')
#: Path to a text file that says 'Hello world!'.
hello_world_path = os.path.join(fixtures_dir, 'hello-world.txt')

#: Serve ``fixtures/hello-world.txt`` file.
static_path = PathDownloadView.as_view(path=hello_world_path)
```

Base options

PathDownloadView inherits from DownloadMixin, which has various options such as basename or attachment.

Computing path dynamically

Override the PathDownloadView.get_path() method to adapt path resolution to your needs:

```
import os

from django_downloadview import PathDownloadView

# Let's initialize some fixtures.
app_dir = os.path.dirname(os.path.abspath(__file__))
project_dir = os.path.dirname(app_dir)
fixtures_dir = os.path.join(project_dir, 'fixtures')

class DynamicPathDownloadView(PathDownloadView):
```

```

"""Serve file in ``settings.MEDIA_ROOT``.

.. warning::

Make sure to prevent "../" in path via URL patterns.

.. note::

This particular setup would be easier to perform with
:class: 'StorageDownloadView'

"""
def get_path(self):
    """Return path inside fixtures directory."""
    # Get path from URL resolvers or as_view kwarg.
    relative_path = super(DynamicPathDownloadView, self).get_path()
    # Make it absolute.
    absolute_path = os.path.join(fixtures_dir, relative_path)
    return absolute_path

```

```
dynamic_path = DynamicPathDownloadView.as_view()
```

The view accepts a path argument you can setup either in `as_view` or via `URLconfs`:

```

from django.conf.urls import patterns, url

from demoproject.path import views

urlpatterns = patterns(
    '',
    url(r'^dynamic-path/(?P<path>[a-zA-Z0-9_-]+\.[a-zA-Z0-9]{1,4})$',
        views.dynamic_path,
        name='dynamic_path'),
)

```

API reference

class `django_downloadview.views.path.PathDownloadView` (***kwargs*)

Bases: `django_downloadview.views.base.BaseDownloadView`

Serve a file using filename.

path = None

Server-side name (including path) of the file to serve.

Filename is supposed to be an absolute filename of a file located on the local filesystem.

path_url_kwarg = 'path'

Name of the URL argument that contains path.

get_path()

Return actual path of the file to serve.

Default implementation simply returns view's path.

Override this method if you want custom implementation. As an example, path could be relative and your custom `get_path()` implementation makes it absolute.

`get_file()`

Use path to return wrapper around file to serve.

3.4.4 HTTPDownloadView

`HTTPDownloadView` serves a file given an URL, i.e. it acts like a proxy.

This view is particularly handy when:

- the client does not have access to the file resource, while your Django server does.
- the client does trust your server, your server trusts a third-party, you do not want to bother the client with the third-party.

Simple example

Setup a view to stream files given URL:

```
from django_downloadview import HTTPDownloadView

class SimpleURLDownloadView(HTTPDownloadView):
    def get_url(self):
        """Return URL of hello-world.txt file on GitHub."""
        return 'https://raw.githubusercontent.com/benoitbryon/django-downloadview' \
            '/b7f660c5e3f37d918b106b02c5af7a887acc0111' \
            '/demo/demoproject/download/fixtures/hello-world.txt'

simple_url = SimpleURLDownloadView.as_view()
```

Base options

`HTTPDownloadView` inherits from `DownloadMixin`, which has various options such as `basename` or `attachment`.

API reference

```
class django_downloadview.views.http.HTTPDownloadView(**kwargs)
    Bases: django_downloadview.views.base.BaseDownloadView

    Proxy files that live on remote servers.

    url = u''
        URL to download (the one we are proxying).

    request_kwargs = {}
        Additional keyword arguments for request handler.

    get_request_factory()
        Return request factory to perform actual HTTP request.

        Default implementation returns requests.get() callable.
```

get_request_kwargs()
Return keyword arguments for use with `get_request_factory()`.
Default implementation returns `request_kwargs`.

get_url()
Return remote file URL (the one we are proxying).
Default implementation returns `url`.

get_file()
Return wrapper which has an `url` attribute.

3.4.5 VirtualDownloadView

`VirtualDownloadView` **serves files that do not live on disk**. Use it when you want to stream a file which content is dynamically generated or which lives in memory.

It is all about overriding `VirtualDownloadView.get_file()` method so that it returns a suitable file wrapper...

Note: Current implementation does not support reverse-proxy optimizations, because there is no place reverse-proxy can load files from after Django exited.

Base options

`VirtualDownloadView` inherits from `DownloadMixin`, which has various options such as `basename` or `attachment`.

Serve text (string or unicode) or bytes

Let's consider you build text dynamically, as a bytes or string or unicode object. Serve it with Django's builtin `ContentFile` wrapper:

```
from django.core.files.base import ContentFile

from django_downloadview import VirtualDownloadView

class TextDownloadView(VirtualDownloadView):
    def get_file(self):
        """Return :class: 'django.core.files.base.ContentFile' object."""
        return ContentFile(b"Hello world!\n", name='hello-world.txt')
```

Serve StringIO

`StringIO` object lives in memory. Let's wrap it in some download view via `VirtualFile`:

```
from six import StringIO

from django_downloadview import VirtualDownloadView
from django_downloadview import VirtualFile

class StringIODownloadView(VirtualDownloadView):
```

```
def get_file(self):
    """Return wrapper on ``StringIO`` object."""
    file_obj = StringIO(u"Hello world!\n")
    return VirtualFile(file_obj, name='hello-world.txt')
```

Stream generated content

Let's consider you have a generator function (yield) or an iterator object (`__iter__()`):

```
def generate_hello():
    yield u'Hello '
    yield u'world!'
    yield u'\n'
```

Stream generated content using `VirtualDownloadView`, `VirtualFile` and `StringIteratorIO`:

```
from django_downloadview import VirtualDownloadView
from django_downloadview import VirtualFile
from django_downloadview import StringIteratorIO

class GeneratedDownloadView(VirtualDownloadView):
    def get_file(self):
        """Return wrapper on ``StringIteratorIO`` object."""
        file_obj = StringIteratorIO(generate_hello())
        return VirtualFile(file_obj, name='hello-world.txt')
```

API reference

class `django_downloadview.views.virtual.VirtualDownloadView` (***kwargs*)

Bases: `django_downloadview.views.base.BaseDownloadView`

Serve not-on-disk or generated-on-the-fly file.

Override the `get_file()` method to customize file wrapper.

was_modified_since (*file_instance, since*)

Delegate to file wrapper's `was_modified_since`, or return `True`.

This is the implementation of an edge case: when files are generated on the fly, we cannot guess whether they have been modified or not. If the file wrapper implements `was_modified_since()` method, then we trust it. Otherwise it is safer to suppose that the file has been modified.

This behaviour prevents file size to be computed on the Django side. Because computing file size means iterating over all the file contents, and we want to avoid that whenever possible. As an example, it could reduce all the benefits of working with dynamic file generators... which is a major feature of virtual files.

3.4.6 Make your own view

DownloadMixin

The `django_downloadview.views.DownloadMixin` class is not a view. It is a base class which you can inherit of to create custom download views.

`DownloadMixin` is a base of `BaseDownloadView`, which itself is a base of all other `django_downloadview`'s builtin views.

class `django_downloadview.views.base.DownloadMixin`

Bases: `object`

Placeholders and base implementation to create file download views.

Note: This class does not inherit from `django.views.generic.base.View`.

The `get_file()` method is a placeholder subclasses must implement. Base implementation raises `NotImplementedError`.

Other methods provide a base implementation that use the file wrapper returned by `get_file()`.

response_class

Response class, to be used in `render_to_response()`.

alias of `DownloadResponse`

attachment = True

Whether to return the response as attachment or not.

When `True` (the default), the view returns file “as attachment”, which usually triggers a “Save the file as ...” prompt.

When `False`, the view returns file “inline”, as if it was an element of the current page.

Note: The actual behaviour client-side depends on the browser and its configuration.

In fact, affects the “Content-Disposition” header via `response’s attachment` attribute.

basename = None

Client-side filename, if only file is returned as attachment.

mimetype = None

File’s mime type. If `None` (the default), then the file’s mime type will be guessed via `mimetypes`.

encoding = None

File’s encoding. If `None` (the default), then the file’s encoding will be guessed via `mimetypes`.

get_file()

Return a file wrapper instance.

Raises `FileNotFound` if file does not exist.

get_basename()

Return `basename`.

Override this method if you need more dynamic `basename`.

get_mimetype()

Return `mimetype`.

Override this method if you need more dynamic mime type.

get_encoding()

Return `encoding`.

Override this method if you need more dynamic encoding.

was_modified_since (*file_instance*, *since*)

Return `True` if `file_instance` was modified after `since`.

Uses file wrapper’s `was_modified_since` if available, with value of `since` as positional argument.

Else, fallbacks to default implementation, which uses `django.views.static.was_modified_since()`.

Django's `was_modified_since` function needs a datetime and a size. It is passed `modified_time` and `size` attributes from file wrapper. If file wrapper does not support these attributes (`AttributeError` or `NotImplementedError` is raised), then the file is considered as modified and `True` is returned.

```
not_modified_response (*response_args, **response_kwargs)
    Return django.http.HttpResponseNotModified instance.
```

```
download_response (*response_args, **response_kwargs)
    Return DownloadResponse.
```

```
file_not_found_response()
    Raise Http404.
```

```
render_to_response (*response_args, **response_kwargs)
    Return “download” response (if everything is ok).

    Return file_not_found_response() if file does not exist.
```

Respects the “HTTP_IF_MODIFIED_SINCE” header if any. In that case, uses `was_modified_since()` and `not_modified_response()`.

Else, uses `download_response()` to return a download response.

BaseDownloadView

The `django_downloadview.views.BaseDownloadView` class is a base class to create download views. It inherits `DownloadMixin` and `django.views.generic.base.View`.

The only thing it does is to implement `get`: it triggers `DownloadMixin`'s `render_to_response`.

```
class django_downloadview.views.base.BaseDownloadView (**kwargs)
    Bases: django_downloadview.views.base.DownloadMixin, django.views.generic.base.View

    A base DownloadMixin that implements get().

    get (request, *args, **kwargs)
        Handle GET requests: stream a file.
```

Serving a file inline rather than as attachment

Use `attachment` to make a view serve a file inline rather than as attachment, i.e. to display the file as if it was an internal part of a page rather than triggering “Save file as...” prompt.

See details in `attachment` API documentation.

```
from django_downloadview import ObjectDownloadView
```

```
from demoproject.object.models import Document
```

```
#: Serve 'file' attribute of 'Document' model, inline (not as attachment).
inline_file_view = ObjectDownloadView.as_view(
    model=Document,
    attachment=False)
```

Handling http not modified responses

Sometimes, you know the latest date and time the content was generated at, and you know a new request would generate exactly the same content. In such a case, you should implement `was_modified_since()` in your view.

Note: Default `was_modified_since()` implementation trusts file wrapper’s `was_modified_since` if any. Else (if calling `was_modified_since()` raises `NotImplementedError` or `AttributeError`) it returns `True`, i.e. it assumes the file was modified.

As an example, the download views above always generate “Hello world!”... so, if the client already downloaded it, we can safely return some HTTP “304 Not Modified” response:

```
from django.core.files.base import ContentFile
from django_downloadview import VirtualDownloadView

class TextDownloadView(VirtualDownloadView):
    def get_file(self):
        """Return :class: 'django.core.files.base.ContentFile' object."""
        return ContentFile(u"Hello world!", name='hello-world.txt')

    def was_modified_since(self, file_instance, since):
        return False # Never modified, always u"Hello world!".
```

3.5 Optimize streaming

Some reverse proxies allow applications to delegate actual download to the proxy:

- with Django, manage permissions, generate files...
- let the reverse proxy serve the file.

As a result, you get increased performance: reverse proxies are more efficient than Django at serving static files.

3.5.1 Supported features grid

Supported features depend on backend. Given the file you want to stream, the backend may or may not be able to handle it:

View / File	<i>Nginx</i>	<i>Apache</i>	<i>Lighttpd</i>
<i>PathDownloadView</i>	Yes, local filesystem.	Yes, local filesystem.	Yes, local filesystem.
<i>StorageDownloadView</i>	Yes, local and remote.	Yes, local filesystem.	Yes, local filesystem.
<i>ObjectDownloadView</i>	Yes, local and remote.	Yes, local filesystem.	Yes, local filesystem.
<i>HTTPDownloadView</i>	Yes.	No.	No.
<i>VirtualDownloadView</i>	No.	No.	No.

As an example, *Nginx X-Accel* handles URL for internal redirects, so it can manage `HTTPFile`; whereas *Apache X-Sendfile* handles absolute path, so it can only deal with files on local filesystem.

There are currently no optimizations to stream in-memory files, since they only live on Django side, i.e. they do not persist after Django returned a response. Note: there is a [feature request](https://github.com/benoitbryon/django-downloadview/issues/70) about “local cache” for streamed files ³.

³ <https://github.com/benoitbryon/django-downloadview/issues/70>

3.5.2 How does it work?

View return some `DownloadResponse` instance, which itself carries a *file wrapper*.

django-downloadview provides response middlewares and decorators that are able to capture `DownloadResponse` instances and convert them to `ProxiedDownloadResponse`.

The `ProxiedDownloadResponse` is specific to the reverse-proxy (backend): it tells the reverse proxy to stream some resource.

Note: The feature is inspired by `Django's TemplateResponse`

3.5.3 Available optimizations

Here are optimizations builtin *django_downloadview*:

Nginx

If you serve Django behind Nginx, then you can delegate the file streaming to Nginx and get increased performance:

- lower resources used by Python/Django workers ;
- faster download.

See [Nginx X-accel documentation](#)⁴ for details.

Known limitations

- Nginx needs access to the resource by URL (proxy) or path (location).
- Thus `VirtualFile` and any generated files cannot be streamed by Nginx.

Given a view

Let's consider the following view:

```
import os

from django.conf import settings
from django.core.files.storage import FileSystemStorage

from django_downloadview import StorageDownloadView

storage_dir = os.path.join(settings.MEDIA_ROOT, 'nginx')
storage = FileSystemStorage(location=storage_dir,
                           base_url=''.join([settings.MEDIA_URL, 'nginx/']))

optimized_by_middleware = StorageDownloadView.as_view(storage=storage,
                                                       path='hello-world.txt')
```

⁴ <http://wiki.nginx.org/X-accel>

What is important here is that the files will have an `url` property implemented by storage. Let's setup an optimization rule based on that URL.

Note: It is generally easier to setup rules based on URL rather than based on name in filesystem. This is because path is generally relative to storage, whereas URL usually contains some storage identifier, i.e. it is easier to target a specific location by URL rather than by filesystem name.

Setup XAccelRedirect middlewares

Make sure `django_downloadview.SmartDownloadMiddleware` is in `MIDDLEWARE_CLASSES` of your *Django* settings.

Example:

```
MIDDLEWARE_CLASSES = [
    'django.middleware.common.CommonMiddleware',
    'django.contrib.sessions.middleware.SessionMiddleware',
    'django.middleware.csrf.CsrfViewMiddleware',
    'django.contrib.auth.middleware.AuthenticationMiddleware',
    'django.contrib.messages.middleware.MessageMiddleware',
    'django_downloadview.SmartDownloadMiddleware'
]
```

Then set `django_downloadview.nginx.XAccelRedirectMiddleware` as `DOWNLOADVIEW_BACKEND`:

```
DOWNLOADVIEW_BACKEND = 'django_downloadview.nginx.XAccelRedirectMiddleware'
```

Then register as many `DOWNLOADVIEW_RULES` as you wish:

```
DOWNLOADVIEW_RULES = [
    {
        'source_url': '/media/nginx/',
        'destination_url': '/nginx-optimized-by-middleware/',
    },
]
```

Each item in `DOWNLOADVIEW_RULES` is a dictionary of keyword arguments passed to the middleware factory. In the example above, we capture responses by `source_url` and convert them to internal redirects to `destination_url`.

```
class django_downloadview.nginx.middlewares.XAccelRedirectMiddleware(source_dir=None,
                                                                    source_url=None,
                                                                    destination_url=None,
                                                                    expires=None,
                                                                    with_buffering=None,
                                                                    limit_rate=None,
                                                                    media_root=None,
                                                                    media_url=None)
```

Bases: `django_downloadview.middlewares.ProxiedDownloadMiddleware`

Configurable middleware, for use in decorators or in global middlewares.

Standard Django middlewares are configured globally via settings. Instances of this class are to be configured individually. It makes it possible to use this class as the factory in `django_downloadview.decorators.DownloadDecorator`.

get_redirect_url (*response*)

Return redirect URL for file wrapped into response.

is_download_response (*response*)

Return True for DownloadResponse, except for “virtual” files.

This implementation cannot handle files that live in memory or which are to be dynamically iterated over. So, we capture only responses whose file attribute have either an URL or a file name.

process_response (*request, response*)

Call `process_download_response()` if response is download.

process_download_response (*request, response*)

Replace DownloadResponse instances by NginxDownloadResponse ones.

Per-view setup with `x_accel_redirect` decorator

Middleware should be enough for most use cases, but you may want per-view configuration. For *nginx*, there is `x_accel_redirect`:

`django_downloadview.nginx.decorators.x_accel_redirect` (*view_func, *args, **kwargs*)

Apply XAccelRedirectMiddleware to view_func.

Proxies (**args, **kwargs*) to middleware constructor.

As an example:

```
import os

from django.conf import settings
from django.core.files.storage import FileSystemStorage

from django_downloadview import StorageDownloadView
from django_downloadview.nginx import x_accel_redirect

optimized_by_decorator = x_accel_redirect(
    StorageDownloadView.as_view(storage=storage, path='hello-world.txt'),
    source_url=storage.base_url,
    destination_url='/nginx-optimized-by-decorator/')

```

Test responses with `assert_x_accel_redirect`

Use `assert_x_accel_redirect()` function as a shortcut in your tests.

```
import os

from django.core.files.base import ContentFile
from django.core.urlresolvers import reverse
import django.test

from django_downloadview.nginx import assert_x_accel_redirect

from demoproject.nginx.views import storage, storage_dir

```

```
def setup_file():
    if not os.path.exists(storage_dir):
        os.makedirs(storage_dir)
    storage.save('hello-world.txt', ContentFile(u'Hello world!\n'))

class OptimizedByMiddlewareTestCase(django.test.TestCase):
    def test_response(self):
        """'nginx:optimized_by_middleware' returns X-Accel response."""
        setup_file()
        url = reverse('nginx:optimized_by_middleware')
        response = self.client.get(url)
        assert_x_accel_redirect(
            self,
            response,
            content_type="text/plain; charset=utf-8",
            charset="utf-8",
            basename="hello-world.txt",
            redirect_url="/nginx-optimized-by-middleware/hello-world.txt",
            expires=None,
            with_buffering=None,
            limit_rate=None)

class OptimizedByDecoratorTestCase(django.test.TestCase):
    def test_response(self):
        """'nginx:optimized_by_decorator' returns X-Accel response."""
        setup_file()
        url = reverse('nginx:optimized_by_decorator')
        response = self.client.get(url)
        assert_x_accel_redirect(
            self,
            response,
            content_type="text/plain; charset=utf-8",
            charset="utf-8",
            basename="hello-world.txt",
            redirect_url="/nginx-optimized-by-decorator/hello-world.txt",
            expires=None,
            with_buffering=None,
            limit_rate=None)
```

`django_downloadview.nginx.tests.assert_x_accel_redirect` (*test_case, response, **assertions*)

Make `test_case` assert that `response` is a `XAccelRedirectResponse`.

Optional assertions dictionary can be used to check additional items:

- `basename`: the basename of the file in the response.
- `content_type`: the value of “Content-Type” header.
- `redirect_url`: the value of “X-Accel-Redirect” header.
- `charset`: the value of X-Accel-Charset header.
- `with_buffering`: the value of X-Accel-Buffering header. If `False`, then makes sure that the header disables buffering. If `None`, then makes sure that the header is not set.
- `expires`: the value of X-Accel-Expires header. If `False`, then makes sure that the header disables

expiration. If `None`, then makes sure that the header is not set.

- `limit_rate`: the value of `X-Accel-Limit-Rate` header. If `False`, then makes sure that the header disables limit rate. If `None`, then makes sure that the header is not set.

The tests above assert the *Django* part is OK. Now let's configure *nginx*.

Setup Nginx

See [Nginx X-accel documentation](#)¹ for details.

Here is what you could have in `/etc/nginx/sites-available/default`:

```
charset utf-8;

# Django-powered service.
upstream frontend {
    server 127.0.0.1:8000 fail_timeout=0;
}

server {
    listen 80 default;

    # File-download proxy.
    #
    # Will serve /var/www/files/myfile.tar.gz when passed URI
    # like /optimized-download/myfile.tar.gz
    #
    # See http://wiki.nginx.org/X-accel
    # and https://django-downloadview.readthedocs.org
    #
    location /proxied-download {
        internal;
        # Location to files on disk.
        alias /var/www/files/;
    }

    # Proxy to Django-powered frontend.
    location / {
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header Host $http_host;
        proxy_redirect off;
        proxy_pass http://frontend;
    }
}
```

... where specific configuration is the `location /optimized-download` section.

Note: `/proxied-download` has the `internal` flag, so this location is not available for the client, i.e. users are not able to download files via `/optimized-download/<filename>`.

Assert everything goes fine with healthchecks

Healthchecks are the best way to check the complete setup.

Common issues

Unknown charset "utf-8" to override Add `charset utf-8;` in your nginx configuration file.

`open() "path/to/something" failed (2: No such file or directory)` Check your `settings.NGINX_DOWNLOAD_MIDDLEWARE_MEDIA_ROOT` in Django configuration VS `alias` in nginx configuration: in a standard configuration, they should be equal.

References

Apache

If you serve Django behind Apache, then you can delegate the file streaming to Apache and get increased performance:

- lower resources used by Python/Django workers ;
- faster download.

See [Apache mod_xsendfile documentation](#)⁵ for details.

Known limitations

- Apache needs access to the resource by path on local filesystem.
- Thus only files that live on local filesystem can be streamed by Apache.

Given a view

Let's consider the following view:

```
import os

from django.conf import settings
from django.core.files.storage import FileSystemStorage

from django_downloadview import StorageDownloadView

storage_dir = os.path.join(settings.MEDIA_ROOT, 'apache')
storage = FileSystemStorage(location=storage_dir,
                           base_url=''.join([settings.MEDIA_URL, 'apache/']))

optimized_by_middleware = StorageDownloadView.as_view(storage=storage,
                                                       path='hello-world.txt')
```

What is important here is that the files will have an `url` property implemented by storage. Let's setup an optimization rule based on that URL.

Note: It is generally easier to setup rules based on URL rather than based on name in filesystem. This is because path is generally relative to storage, whereas URL usually contains some storage identifier, i.e. it is easier to target a specific location by URL rather than by filesystem name.

⁵ https://tn123.org/mod_xsendfile/

Setup XSendfile middlewares

Make sure `django_downloadview.SmartDownloadMiddleware` is in `MIDDLEWARE_CLASSES` of your *Django* settings.

Example:

```
MIDDLEWARE_CLASSES = [
    'django.middleware.common.CommonMiddleware',
    'django.contrib.sessions.middleware.SessionMiddleware',
    'django.middleware.csrf.CsrfViewMiddleware',
    'django.contrib.auth.middleware.AuthenticationMiddleware',
    'django.contrib.messages.middleware.MessageMiddleware',
    'django_downloadview.SmartDownloadMiddleware'
]
```

Then set `django_downloadview.apache.XSendfileMiddleware` as `DOWNLOADVIEW_BACKEND`:

```
DOWNLOADVIEW_BACKEND = 'django_downloadview.apache.XSendfileMiddleware'
```

Then register as many `DOWNLOADVIEW_RULES` as you wish:

```
DOWNLOADVIEW_RULES = [
    {
        'source_url': '/media/apache/',
        'destination_dir': '/apache-optimized-by-middleware/',
    },
]
```

Each item in `DOWNLOADVIEW_RULES` is a dictionary of keyword arguments passed to the middleware factory. In the example above, we capture responses by `source_url` and convert them to internal redirects to `destination_dir`.

```
class django_downloadview.apache.middlewares.XSendfileMiddleware (source_dir=None,
                                                                source_url=None,
                                                                destina-
                                                                tion_dir=None)

Bases: django_downloadview.middlewares.ProxiedDownloadMiddleware
```

Configurable middleware, for use in decorators or in global middlewares.

Standard Django middlewares are configured globally via settings. Instances of this class are to be configured individually. It makes it possible to use this class as the factory in `django_downloadview.decorators.DownloadDecorator`.

process_download_response (*request*, *response*)

Replace `DownloadResponse` instances by `XSendfileResponse` ones.

get_redirect_url (*response*)

Return redirect URL for file wrapped into response.

is_download_response (*response*)

Return True for `DownloadResponse`, except for “virtual” files.

This implementation cannot handle files that live in memory or which are to be dynamically iterated over. So, we capture only responses whose file attribute have either an URL or a file name.

process_response (*request*, *response*)

Call `process_download_response()` if response is download.

Per-view setup with `x_sendfile` decorator

Middleware should be enough for most use cases, but you may want per-view configuration. For *Apache*, there is `x_sendfile`:

```
django_downloadview.apache.decorators.x_sendfile (view_func, *args, **kwargs)
```

Apply `XSendfileMiddleware` to `view_func`.

Proxies (`*args, **kwargs`) to middleware constructor.

As an example:

```
import os

from django.conf import settings
from django.core.files.storage import FileSystemStorage

from django_downloadview import StorageDownloadView
from django_downloadview.apache import x_sendfile

optimized_by_decorator = x_sendfile(
    StorageDownloadView.as_view(storage=settings.STORAGE, path='hello-world.txt'),
    source_url=settings.MEDIA_URL,
    destination_dir='/apache-optimized-by-decorator/')
```

Test responses with `assert_x_sendfile`

Use `assert_x_sendfile()` function as a shortcut in your tests.

```
import os

from django.core.files.base import ContentFile
from django.core.urlresolvers import reverse
import django.test

from django_downloadview.apache import assert_x_sendfile
from demoproject.apache.views import storage, storage_dir

def setup_file():
    if not os.path.exists(storage_dir):
        os.makedirs(storage_dir)
    storage.save('hello-world.txt', ContentFile(u'Hello world!\n'))

class OptimizedByMiddlewareTestCase(django.test.TestCase):
    def test_response(self):
        """'apache:optimized_by_middleware' returns X-Sendfile response."""
        setup_file()
        url = reverse('apache:optimized_by_middleware')
        response = self.client.get(url)
        assert_x_sendfile(
            self,
            response,
            content_type="text/plain; charset=utf-8",
            basename="hello-world.txt",
```

```
file_path="/apache-optimized-by-middleware/hello-world.txt")
```

```
class OptimizedByDecoratorTestCase(django.test.TestCase):
    def test_response(self):
        """'apache:optimized_by_decorator' returns X-Sendfile response."""
        setup_file()
        url = reverse('apache:optimized_by_decorator')
        response = self.client.get(url)
        assert_x_sendfile(
            self,
            response,
            content_type="text/plain; charset=utf-8",
            basename="hello-world.txt",
            file_path="/apache-optimized-by-decorator/hello-world.txt")

django_downloadview.apache.tests.assert_x_sendfile(test_case, response, **assertions)
Make test_case assert that response is a XSendfileResponse.
```

Optional assertions dictionary can be used to check additional items:

- `basename`: the basename of the file in the response.
- `content_type`: the value of “Content-Type” header.
- `file_path`: the value of “X-Sendfile” header.

The tests above assert the *Django* part is OK. Now let’s configure *Apache*.

Setup Apache

See [Apache `mod_xsendfile` documentation](#)¹ for details.

Assert everything goes fine with healthchecks

Healthchecks are the best way to check the complete setup.

References

Lighttpd

If you serve Django behind *Lighttpd*, then you can delegate the file streaming to *Lighttpd* and get increased performance:

- lower resources used by Python/Django workers ;
- faster download.

See [Lighttpd X-Sendfile documentation](#)⁶ for details.

Note: Currently, *django_downloadview* supports X-Sendfile, but not X-Sendfile2. If you need X-Sendfile2 or know how to handle it, check [X-Sendfile2 feature request](#) on *django_downloadview*’s bugtracker⁷.

⁶ <http://redmine.lighttpd.net/projects/lighttpd/wiki/X-LIGHTTPD-send-file>

⁷ <https://github.com/benoitbryon/django-downloadview/issues/67>

Known limitations

- Lighttpd needs access to the resource by path on local filesystem.
- Thus only files that live on local filesystem can be streamed by Lighttpd.

Given a view

Let's consider the following view:

```
import os

from django.conf import settings
from django.core.files.storage import FileSystemStorage

from django_downloadview import StorageDownloadView

storage_dir = os.path.join(settings.MEDIA_ROOT, 'lighttpd')
storage = FileSystemStorage(
    location=storage_dir,
    base_url=''.join([settings.MEDIA_URL, 'lighttpd/']))

optimized_by_middleware = StorageDownloadView.as_view(storage=storage,
                                                       path='hello-world.txt')
```

What is important here is that the files will have an `url` property implemented by storage. Let's setup an optimization rule based on that URL.

Note: It is generally easier to setup rules based on URL rather than based on name in filesystem. This is because path is generally relative to storage, whereas URL usually contains some storage identifier, i.e. it is easier to target a specific location by URL rather than by filesystem name.

Setup XSendfile middlewares

Make sure `django_downloadview.SmartDownloadMiddleware` is in `MIDDLEWARE_CLASSES` of your *Django* settings.

Example:

```
MIDDLEWARE_CLASSES = [
    'django.middleware.common.CommonMiddleware',
    'django.contrib.sessions.middleware.SessionMiddleware',
    'django.middleware.csrf.CsrfViewMiddleware',
    'django.contrib.auth.middleware.AuthenticationMiddleware',
    'django.contrib.messages.middleware.MessageMiddleware',
    'django_downloadview.SmartDownloadMiddleware'
]
```

Then set `django_downloadview.lighttpd.XSendfileMiddleware` as `DOWNLOADVIEW_BACKEND`:

```
DOWNLOADVIEW_BACKEND = 'django_downloadview.lighttpd.XSendfileMiddleware'
```

Then register as many `DOWNLOADVIEW_RULES` as you wish:

```
DOWNLOADVIEW_RULES = [
    {
        'source_url': '/media/lighttpd/',
        'destination_dir': '/lighttpd-optimized-by-middleware/',
    },
]
```

Each item in `DOWNLOADVIEW_RULES` is a dictionary of keyword arguments passed to the middleware factory. In the example above, we capture responses by `source_url` and convert them to internal redirects to `destination_dir`.

```
class django_downloadview.lighttpd.middlewares.XSendfileMiddleware (source_dir=None,
                                                                    source_url=None,
                                                                    destina-
                                                                    tion_dir=None)

Bases: django_downloadview.middlewares.ProxiedDownloadMiddleware
```

Configurable middleware, for use in decorators or in global middlewares.

Standard Django middlewares are configured globally via settings. Instances of this class are to be configured individually. It makes it possible to use this class as the factory in `django_downloadview.decorators.DownloadDecorator`.

process_download_response (*request, response*)
Replace `DownloadResponse` instances by `XSendfileResponse` ones.

get_redirect_url (*response*)
Return redirect URL for file wrapped into response.

is_download_response (*response*)
Return True for `DownloadResponse`, except for “virtual” files.

This implementation cannot handle files that live in memory or which are to be dynamically iterated over. So, we capture only responses whose file attribute have either an URL or a file name.

process_response (*request, response*)
Call `process_download_response()` if response is download.

Per-view setup with `x_sendfile` decorator

Middlewares should be enough for most use cases, but you may want per-view configuration. For *Lighttpd*, there is `x_sendfile`:

```
django_downloadview.lighttpd.decorators.x_sendfile (view_func, *args, **kwargs)
    Apply XSendfileMiddleware to view_func.
```

Proxies (**args, **kwargs*) to middleware constructor.

As an example:

```
import os

from django.conf import settings
from django.core.files.storage import FileSystemStorage

from django_downloadview import StorageDownloadView
from django_downloadview.lighttpd import x_sendfile
```

```
optimized_by_decorator = x_sendfile(
```

```
StorageDownloadView.as_view(storage=storage, path='hello-world.txt'),
source_url=storage.base_url,
destination_dir='/lighttpd-optimized-by-decorator/')
```

Test responses with `assert_x_sendfile`

Use `assert_x_sendfile()` function as a shortcut in your tests.

```
import os

from django.core.files.base import ContentFile
from django.core.urlresolvers import reverse
import django.test

from django_downloadview.lighttpd import assert_x_sendfile

from demoproject.lighttpd.views import storage, storage_dir

def setup_file():
    if not os.path.exists(storage_dir):
        os.makedirs(storage_dir)
    storage.save('hello-world.txt', ContentFile(u'Hello world!\n'))

class OptimizedByMiddlewareTestCase(django.test.TestCase):
    def test_response(self):
        """'lighttpd:optimized_by_middleware' returns X-Sendfile response."""
        setup_file()
        url = reverse('lighttpd:optimized_by_middleware')
        response = self.client.get(url)
        assert_x_sendfile(
            self,
            response,
            content_type="text/plain; charset=utf-8",
            basename="hello-world.txt",
            file_path="/lighttpd-optimized-by-middleware/hello-world.txt")

class OptimizedByDecoratorTestCase(django.test.TestCase):
    def test_response(self):
        """'lighttpd:optimized_by_decorator' returns X-Sendfile response."""
        setup_file()
        url = reverse('lighttpd:optimized_by_decorator')
        response = self.client.get(url)
        assert_x_sendfile(
            self,
            response,
            content_type="text/plain; charset=utf-8",
            basename="hello-world.txt",
            file_path="/lighttpd-optimized-by-decorator/hello-world.txt")

django_downloadview.lighttpd.tests.assert_x_sendfile(test_case, response, **assertions)
```

Make `test_case` assert that `response` is a `XSendfileResponse`.

Optional assertions dictionary can be used to check additional items:

- `basename`: the basename of the file in the response.
- `content_type`: the value of “Content-Type” header.
- `file_path`: the value of “X-Sendfile” header.

The tests above assert the *Django* part is OK. Now let’s configure *Lighttpd*.

Setup Lighttpd

See [Lighttpd X-Sendfile documentation](#)¹ for details.

Assert everything goes fine with healthchecks

Healthchecks are the best way to check the complete setup.

References

Note: If you need support for additional optimizations, tell us⁸!

Notes & references

3.6 Write tests

django_downloadview embeds test utilities:

- `temporary_media_root()`
- `assert_download_response()`
- `setup_view()`
- `assert_x_accel_redirect()`

3.6.1 temporary_media_root

`django_downloadview.test.temporary_media_root(**kwargs)`
Temporarily override `settings.MEDIA_ROOT` with a temporary directory.

The temporary directory is automatically created and destroyed.

Use this function as a context manager:

```
>>> from django_downloadview.test import temporary_media_root
>>> from django.conf import settings # NoQA
>>> global_media_root = settings.MEDIA_ROOT
>>> with temporary_media_root():
...     global_media_root == settings.MEDIA_ROOT
False
>>> global_media_root == settings.MEDIA_ROOT
True
```

⁸ <https://github.com/benoitbryon/django-downloadview/issues?labels=optimizations>

Or as a decorator:

```
>>> @temporary_media_root()
... def use_temporary_media_root():
...     return settings.MEDIA_ROOT
>>> tmp_media_root = use_temporary_media_root()
>>> global_media_root == tmp_media_root
False
>>> global_media_root == settings.MEDIA_ROOT
True
```

3.6.2 assert_download_response

`django_downloadview.test.assert_download_response(test_case, response, **assertions)`

Make `test_case` assert that response meets assertions.

Optional assertions dictionary can be used to check additional items:

- `basename`: the basename of the file in the response.
- `content_type`: the value of “Content-Type” header.
- `mime_type`: the MIME type part of “Content-Type” header (without charset).
- `content`: the contents of the file.
- `attachment`: whether the file is returned as attachment or not.

Examples, related to *StorageDownloadView* demo:

```
from django.core.files.base import ContentFile
from django.core.urlresolvers import reverse
import django.test

from django_downloadview import assert_download_response, temporary_media_root

from demoproject.storage import views

# Fixtures.
file_content = 'Hello world!\n'

def setup_file(path):
    views.storage.save(path, ContentFile(file_content))

class StaticPathTestCase(django.test.TestCase):
    @temporary_media_root()
    def test_download_response(self):
        """'storage:static_path' streams file by path."""
        setup_file('1.txt')
        url = reverse('storage:static_path', kwargs={'path': '1.txt'})
        response = self.client.get(url)
        assert_download_response(self,
                                response,
                                content=file_content,
                                basename='1.txt',
                                mime_type='text/plain')
```



```

class DynamicPathIntegrationTestCase(django.test.TestCase):
    """Integration tests around 'storage:dynamic_path' URL."""
    @temporary_media_root()
    def test_download_response(self):
        """'dynamic_path' streams file by generated path.

        As we use 'self.client', this test involves the whole Django stack,
        including settings, middlewares, decorators... So we need to setup a
        file, the storage, and an URL.

        This test actually asserts the URL 'storage:dynamic_path' streams a
        file in storage.

        """
        setup_file('1.TXT')
        url = reverse('storage:dynamic_path', kwargs={'path': '1.txt'})
        response = self.client.get(url)
        assert_download_response(self,
                                response,
                                content=file_content,
                                basename='1.TXT',
                                mime_type='text/plain')

```

3.6.3 setup_view

`django_downloadview.test.setup_view(view, request, *args, **kwargs)`

Mimic `as_view()`, but returns view instance.

Use this function to get view instances on which you can run unit tests, by testing specific methods.

This is an early implementation of <https://code.djangoproject.com/ticket/20456>

view A view instance, such as `TemplateView(template_name='dummy.html')`. Initialization arguments are the same you would pass to `as_view()`.

request A request object, typically built with `RequestFactory`.

args and kwargs “URLconf” positional and keyword arguments, the same you would pass to `reverse()`.

Example, related to *StorageDownloadView* demo:

```

import unittest

from django_downloadview import setup_view

from demoproject.storage import views

class DynamicPathUnitTestCase(unittest.TestCase):
    """Unit tests around 'views.DynamicStorageDownloadView'."""
    def test_get_path(self):
        """DynamicStorageDownloadView.get_path() returns uppercase path.

        Uses :func:`~django_downloadview.test.setup_view` to target only
        overridden methods.

        This test does not involve URLconf, middlewares or decorators. It is
        fast. It has clear scope. It does not assert 'storage:dynamic_path'

```

```
URL works. It targets only custom ``DynamicStorageDownloadView`` class.

"""
view = setup_view(views.DynamicStorageDownloadView(),
                  django.test.RequestFactory().get('/fake-url'),
                  path='dummy path')
path = view.get_path()
self.assertEqual(path, 'DUMMY PATH')
```

3.7 Write healthchecks

In the previous *testing* topic, you made sure the views and middlewares work as expected... within a test environment. One common issue when deploying in production is that the reverse-proxy's configuration does not fit. You cannot check that within test environment.

Healthchecks are made to diagnose issues in live (production) environments.

3.7.1 Introducing healthchecks

Healthchecks (sometimes called “smoke tests” or “diagnosis”) are assertions you run on a live (typically production) service, as opposed to fake/mock service used during tests (unit, integration, functional).

See [hospital](#)⁹ and [django-doctor](#)¹⁰ projects about writing healthchecks for Python and Django.

3.7.2 Typical healthchecks

Here is a typical healthcheck setup for download views with reverse-proxy optimizations.

When you run this healthcheck suite, you get a good overview if a problem occurs: you can compare expected results and learn which part (Django, reverse-proxy or remote storage) is guilty.

Note: In the examples below, we use “localhost” and ports “80” (reverse-proxy) or “8000” (Django). Adapt them to your configuration.

Check storage

Put a dummy file on the storage Django uses.

The write a healthcheck that asserts you can read the dummy file from storage.

On success, you know remote storage is ok.

Issues may involve permissions or communications (remote storage).

Note: This healthcheck may be outside Django.

⁹ <https://pypi.python.org/pypi/hospital>

¹⁰ <https://pypi.python.org/pypi/django-doctor>

Check Django VS storage

Implement a download view dedicated to healthchecks. It is typically a public (but not referenced) view that streams a dummy file from real storage. Let's say you register it as `/healthcheck-utils/download/` URL.

Write a healthcheck that asserts `GET http://localhost:8000/healthcheck-utils/download/` (notice the `8000` port: local Django server) returns the expected reverse-proxy response (X-Accel, X-Sendfile...).

On success, you know there is no configuration issue on the Django side.

Check reverse proxy VS storage

Write a location in your reverse-proxy's configuration that proxy-pass to a dummy file on storage.

Write a healthcheck that asserts this location returns the expected dummy file.

On success, you know the reverse proxy can serve files from storage.

Check them all together

We just checked all parts separately, so let's make sure they can work together. Configure the reverse-proxy so that `/healthcheck-utils/download/` is proxied to Django. Then write a healthcheck that asserts `GET http://localhost:80/healthcheck-utils/download` (notice the `80` port: reverse-proxy server) returns the expected dummy file.

On success, you know everything is ok.

On failure, there is an issue in the X-Accel/X-Sendfile configuration.

Note: This last healthcheck should be the first one to run, i.e. if it passes, others should pass too. The others are useful when this one fails.

Notes & references

3.8 File wrappers

A view return `DownloadResponse` which itself carries a file wrapper. Here are file wrappers distributed by Django and `django-downloadview`.

3.8.1 Django's builtins

Django itself provides some file wrappers ¹¹ you can use within `django-downloadview`:

- `django.core.files.File` wraps a file that live on local filesystem, initialized with a path. `django-downloadview` uses this wrapper in `PathDownloadView`.
- `django.db.models.fields.files.FieldFile` wraps a file that is managed in a model. `django-downloadview` uses this wrapper in `ObjectDownloadView`.
- `django.core.files.base.ContentFile` wraps a bytes, string or unicode object. You may use it with `VirtualDownloadView`.

¹¹ <https://docs.djangoproject.com/en/1.5/ref/files/file/>

3.8.2 django-downloadview builtins

django-downloadview implements additional file wrappers:

- `StorageFile` wraps a file that is managed via a storage (but not necessarily via a model). *StorageDownloadView* uses this wrapper.
- `HTTPFile` wraps a file that lives at some (remote) location, initialized with an URL. *HTTPDownloadView* uses this wrapper.
- `VirtualFile` wraps a file that lives in memory, i.e. built as a string. This is a convenient wrapper to use in *VirtualDownloadView* subclasses.

3.8.3 API reference

StorageFile

class `django_downloadview.files.StorageFile` (*storage*, *name*, *file=None*)

Bases: `django.core.files.base.File`

A file in a Django storage.

This class looks like `django.db.models.fields.files.FieldFile`, but unrelated to model instance.

file

Required by `django.core.files.utils.FileProxy`.

open (*mode='rb'*)

Retrieves the specified file from storage and return `open()` result.

Proxy to `self.storage.open(self.name, mode)`.

save (*content*)

Saves new content to the file.

Proxy to `self.storage.save(self.name)`.

The content should be a proper File object, ready to be read from the beginning.

path

Return a local filesystem path which is suitable for `open()`.

Proxy to `self.storage.path(self.name)`.

May raise `NotImplementedError` if storage doesn't support file access with Python's built-in `open()` function

delete ()

Delete the specified file from the storage system.

Proxy to `self.storage.delete(self.name)`.

exists ()

Return True if file already exists in the storage system.

If False, then the name is available for a new file.

size

Return the total size, in bytes, of the file.

Proxy to `self.storage.size(self.name)`.

url

Return an absolute URL where the file's contents can be accessed.

Proxy to `self.storage.url(self.name)`.

accessed_time

Return the last accessed time (as datetime object) of the file.

Proxy to `self.storage.accessed_time(self.name)`.

created_time

Return the creation time (as datetime object) of the file.

Proxy to `self.storage.created_time(self.name)`.

modified_time

Return the last modification time (as datetime object) of the file.

Proxy to `self.storage.modified_time(self.name)`.

HTTPFile

```
class django_downloadview.files.HTTPFile (request_factory=<function get at 0x2fc0c08>,
                                           url='', name=u'', **kwargs)
```

Bases: `django.core.files.base.File`

Wrapper for files that live on remote HTTP servers.

Acts as a proxy.

Uses <https://pypi.python.org/pypi/requests>.

Always sets “stream=True” in requests kwargs.

request**file****size**

Return the total size, in bytes, of the file.

Reads response's “content-length” header.

VirtualFile

```
class django_downloadview.files.VirtualFile (file=None, name=u'', url='', size=None)
```

Bases: `django.core.files.base.File`

Wrapper for files that live in memory.

size

Notes & references

3.9 Responses

Views return `DownloadResponse`.

Middlewares (and decorators) are given the opportunity to capture responses and convert them to `ProxiedDownloadResponse`.

3.9.1 DownloadResponse

```
class django_downloadview.response.DownloadResponse (file_instance,      attachment=True,
                                                    basename=None,        sta-
                                                    tus=200,        content_type=None,
                                                    file_mimetype=None,
                                                    file_encoding=None)
```

Bases: `django.http.response.StreamingHttpResponse`

File download response (Django serves file, client downloads it).

This is a specialization of `django.http.StreamingHttpResponse` where `streaming_content` is a file wrapper.

Constructor differs a bit from `HttpResponse`.

Here are some highlights to understand internal mechanisms and motivations:

- Let's start by quoting **PEP 3333** (WSGI specification):

For large files, or for specialized uses of HTTP streaming, applications will usually return an iterator (often a generator-iterator) that produces the output in a block-by-block fashion.

- Django WSGI handler (application implementation) returns response object (see `django.core.handlers.wsgi`).

- `django.http.HttpResponse` and subclasses are iterators.

- In `StreamingHttpResponse`, the `__iter__()` implementation proxies to `streaming_content`.

- In `DownloadResponse` and subclasses, `streaming_content` is a *file wrapper*. File wrapper is itself an iterator over actual file content, and it also encapsulates access to file attributes (size, name, ...).

file = None

A file wrapper instance, such as `File`.

basename = None

Client-side name of the file to stream. Only used if `attachment` is `True`. Affects `Content-Disposition` header.

attachment = None

Whether to return the file as attachment or not. Affects `Content-Disposition` header.

file_mimetype = None

Value for file's mimetype. If `None` (the default), then the file's mimetype will be guessed via Python's `mimetypes`. See `get_mime_type()`.

file_encoding = None

Value for file's encoding. If `None` (the default), then the file's encoding will be guessed via Python's `mimetypes`. See `get_encoding()`.

default_headers

Return dictionary of automatically-computed headers.

Uses an internal `_default_headers` cache. Default values are computed if only cache hasn't been set.

`Content-Disposition` header is encoded according to **RFC 5987**. See also <http://stackoverflow.com/questions/93551/>.

items()

Return iterable of (header, value).

This method is called by http handlers just before WSGI's `start_response()` is called... but it is not called by `django.test.ClientHandler!` :(

```

get_basename()
    Return basename.

get_content_type()
    Return a suitable "Content-Type" header for self.file.

get_mime_type()
    Return mime-type of the file.

get_encoding()
    Return encoding of the file to serve.

get_charset()
    Return the charset of the file to serve.

```

3.9.2 ProxiedDownloadResponse

```

class django_downloadview.response.ProxiedDownloadResponse (content='', *args,
                                                            **kwargs)

```

Bases: `django.http.response.HttpResponse`

Base class for internal redirect download responses.

This base class makes it possible to identify several types of specific responses such as `XAccelRedirectResponse`.

3.10 Migrating from django-sendfile

`django-sendfile` ¹² is a wrapper around web-server specific methods for sending files to web clients. See *Alternatives and related projects* for details about this project.

`django-downloadview` provides a port of `django-sendfile`'s main function.

Warning: `django-downloadview` can replace the following `django-sendfile`'s backends: `nginx`, `xsendfile`, `simple`. But it currently cannot replace `mod_wsgi` backend.

Here are tips to migrate from `django-sendfile` to `django-downloadview`...

1. In your project's and apps dependencies, replace `django-sendfile` by `django-downloadview`.
2. In your Python scripts, replace `import sendfile` and `from sendfile` by `import django_downloadview` and `from django_downloadview`. You get something like `from django_downloadview import sendfile`
3. Adapt your settings as explained in *Configure*. Pay attention to:
 - replace `sendfile` by `django_downloadview` in `INSTALLED_APPS`.
 - replace `SENDFILE_BACKEND` by `DOWNLOADVIEW_BACKEND`
 - setup `DOWNLOADVIEW_RULES`. It replaces `SENDFILE_ROOT` and can do more.
 - register `django_downloadview.SmartDownloadMiddleware` in `MIDDLEWARE_CLASSES`.

¹² <http://pypi.python.org/pypi/django-sendfile>

4. Change your tests if any. You can no longer use *django-sendfile*'s development backend. See *Write tests* for *django-downloadview*'s toolkit.
5. Here you are! ... or please report your story/bug at *django-downloadview*'s [bugtracker](#) ¹³ ;)

3.10.1 API reference

`django_downloadview.shortcuts.sendfile(request, filename, attachment=False, attachment_filename=None, mimetype=None, encoding=None)`

Port of *django-sendfile*'s API in *django-downloadview*.

Instantiates a `PathDownloadView` to stream the file by `filename`.

References

3.11 Demo project

Demo folder in project's repository ¹⁴ contains a Django project to illustrate *django-downloadview* usage.

3.11.1 Documentation includes code from the demo

Almost every example in the documentation comes from the demo:

- discover examples in the documentation;
- browse related code and tests in demo project.

Examples in documentation are tested via demo project!

3.11.2 Browse demo code online

See [demo folder in project's repository](#) ¹.

3.11.3 Deploy the demo

System requirements:

- [Python](#) ¹⁵ version 2.7, available as `python` command.

Note: You may use [Virtualenv](#) ¹⁶ to make sure the active python is the right one.

- `make` and `wget` to use the provided `Makefile`.

Execute:

```
git clone git@github.com:benoitbryon/django-downloadview.git
cd django-downloadview/
make runserver
```

¹³ <https://github.com/benoitbryon/django-downloadview/issues>

¹⁴ <https://github.com/benoitbryon/django-downloadview/tree/master/demo/demoproject/>

¹⁵ <http://python.org>

¹⁶ <http://virtualenv.org>

It installs and runs the demo server on localhost, port 8000. So have a look at <http://localhost:8000/>

Note: If you cannot execute the Makefile, read it and adapt the few commands it contains to your needs.

Browse and use `demo/demoproject/` as a sandbox.

3.11.4 References

3.12 About django-downloadview

3.12.1 Vision

django-downloadview tries to simplify the development of “download” views using Django ¹⁷ framework. It provides generic views that cover most common patterns.

Django is not the best solution to serve files: reverse proxies are far more efficient. *django-downloadview* makes it easy to implement this best-practice.

Tests matter: *django-downloadview* provides tools to test download views and optimizations.

Notes & references

See also:

- *Alternatives and related projects*
- [roadmap](#)

3.12.2 Alternatives and related projects

This document presents other projects that provide similar or complementary functionalities. It focuses on differences with *django-downloadview*.

There is a comparison grid on djangopackages.com: <https://www.djangopackages.com/grids/g/file-streaming/>.

Here are additional highlights...

Django’s static file view

`django.contrib.staticfiles` provides a view to serve files ¹⁸. It is simple and quite naive by design: it is meant for development, not for production. See Django ticket #2131 ¹⁹: advanced file streaming is left to third-party applications.

django-downloadview is such a third-party application.

¹⁷ <https://django-project.com>

¹⁸ <https://docs.djangoproject.com/en/1.6/ref/contrib/staticfiles/#static-file-development-view>

¹⁹ <https://code.djangoproject.com/ticket/2131>

django-sendfile

django-sendfile²⁰ is a wrapper around web-server specific methods for sending files to web clients.

Note: `django_downloadview.shortcuts.sendfile()` is a port of *django-sendfile*'s main function. See *Migrating from django-sendfile* for details.

django-sendfile's main focus is simplicity: API is made of a single `sendfile()` function you call inside your views:

```
from sendfile import sendfile

def hello_world(request):
    """Send 'hello-world.pdf' file as a response."""
    return sendfile(request, '/path/to/hello-world.pdf')
```

The download response type depends on the chosen backend, which could be Django, Lighttpd's X-Sendfile, Nginx's X-Accel... depending your settings:

```
SENDFILE_BACKEND = 'sendfile.backends.nginx' # sendfile() will return
                                              # X-Accel responses.

# Additional settings for sendfile's nginx backend.
SENDFILE_ROOT = '/path/to'
SENDFILE_URL = '/proxied-download'
```

Here are main differences between the two projects:

- django-sendfile supports only files that live on local filesystem (i.e. where `os.path.exists` returns `True`). Whereas django-downloadview allows you to serve or proxy files stored in various locations, including remote ones.
- django-sendfile uses a single global configuration (i.e. `settings.SENDFILE_ROOT`), thus optimizations are limited to a single root folder. Whereas django-downloadview's `DownloadDispatcherMiddleware` supports multiple configurations.

References

3.12.3 License

Copyright (c) 2012-2014, Benoît Bryon. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of django-downloadview nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT

²⁰ <http://pypi.python.org/pypi/django-sendfile>

SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

3.12.4 Authors & contributors

Maintainer: Benoît Bryon <benoit@marmelune.net>

Original code by Novapost team:

- Nicolas Tobo <<https://github.com/nicolastobo>>
- Lauréline Guérin <<https://github.com/zebuline>>
- Gregory Tappero <<https://github.com/coulix>>
- Rémy Hubscher <remy.hubscher@novapost.fr>
- Benoît Bryon <benoit@marmelune.net>

Developers: <https://github.com/benoitbryon/django-downloadview/graphs/contributors>

3.12.5 Changelog

This document describes changes between past releases. For information about future releases, check [milestones](#) ²¹ and *Vision*.

1.6 (2014-03-03)

Python 3 support, development environment refactoring.

- Feature #46: introduced support for Python>=3.3.
- Feature #80: added documentation about “how to serve a file inline VS how to serve a file as attachment”. Improved documentation of views’ base options inherited from `DownloadMixin`.
- Feature #74: the Makefile in project’s repository no longer creates a virtualenv. Developers setup the environment as they like, i.e. using virtualenv, virtualenvwrapper or whatever. Tests are run with tox.

1.5 (2013-11-29)

X-Sendfile support and helpers to migrate for *django-sendfile*.

- Feature #2 - Introduced support of Lighttpd’s x-Sendfile.
- Feature #36 - Introduced support of Apache’s mod_xsendfile.
- Feature #41 - `django_downloadview.sendfile` is a port of *django-sendfile*’s `sendfile` function. The documentation contains notes about migrating from *django-sendfile* to *django-downloadview*.

²¹ <https://github.com/benoitbryon/django-downloadview/issues/milestones>

1.4 (2013-11-24)

Bugfixes and documentation features.

- Bugfix #43 - `ObjectDownloadView` returns HTTP 404 if model instance's file field is empty (was HTTP 500).
- Bugfix #7 - Special characters in file names (`Content-Disposition` header) are urlencoded. An US-ASCII fallback is also provided.
- Feature #10 - *django-downloadview* is registered on djangopackages.com.
- Feature #65 - INSTALL documentation shows “known good set” (KGS) of versions, i.e. versions that have been used in test environment.

1.3 (2013-11-08)

Big refactoring around middleware configuration, API readability and documentation.

- Bugfix #57 - `PathDownloadView` opens files in binary mode (was text mode).
- Bugfix #48 - Fixed `basename` assertion in `assert_download_response:` checks `Content-Disposition` header.
- Bugfix #49 - Fixed content assertion in `assert_download_response:` checks only response's `streaming_content` attribute.
- Bugfix #60 - `VirtualFile.__iter__` uses `force_bytes()` to support both “text-mode” and “binary-mode” content. See <https://code.djangoproject.com/ticket/21321>
- Feature #50 - Introduced `django_downloadview.DownloadDispatcherMiddleware` that iterates over a list of configurable download middlewares. Allows to plug several download middlewares with different configurations.

This middleware is mostly dedicated to internal usage. It is used by `SmartDownloadMiddleware` described below.

- Feature #42 - Documentation shows how to stream generated content (yield). Introduced `django_downloadview.StringIteratorIO`.
- Refactoring #51 - Dropped support of Python 2.6
- Refactoring #25 - Introduced `django_downloadview.SmartDownloadMiddleware` which allows to setup multiple optimization rules for one backend.

Deprecates the following settings related to previous single-and-global middleware:

- `NGINX_DOWNLOAD_MIDDLEWARE_MEDIA_ROOT`
- `NGINX_DOWNLOAD_MIDDLEWARE_MEDIA_URL`
- `NGINX_DOWNLOAD_MIDDLEWARE_EXPIRES`
- `NGINX_DOWNLOAD_MIDDLEWARE_WITH_BUFFERING`
- `NGINX_DOWNLOAD_MIDDLEWARE_LIMIT_RATE`

- Refactoring #52 - `ObjectDownloadView` now inherits from `SingleObjectMixin` and `BaseDownloadView` (was `DownloadMixin` and `BaseDetailView`). Simplified `DownloadMixin.render_to_response()` signature.
- Refactoring #40 - Documentation includes examples from demo project.
- Refactoring #39 - Documentation focuses on usage, rather than API. Improved narrative documentation.

- Refactoring #53 - Added base classes in `django_downloadview.middlewares`, such as `ProxiedDownloadMiddleware`.
- Refactoring #54 - Expose most Python API directly in *django_downloadview* package. Simplifies import statements in client applications. Splitted nginx module in a package.
- Added unit tests, improved code coverage.

1.2 (2013-05-28)

Bugfixes and documentation improvements.

- Bugfix #26 - Prevented computation of virtual file's size, unless the file wrapper implements `was_modified_since()` method.
- Bugfix #34 - Improved support of files that do not implement modification time.
- Bugfix #35 - Fixed README conversion from reStructuredText to HTML (PyPI).

1.1 (2013-04-11)

Various improvements. Contains **backward incompatible changes**.

- Added `HTTPDownloadView` to proxy to arbitrary URL.
- Added `VirtualDownloadView` to support files living in memory.
- Using `StreamingHttpResponse` introduced with Django 1.5. Makes Django 1.5 a requirement!
- Added `django_downloadview.test.assert_download_response` utility.
- Download views and response now use file wrappers. Most logic around file attributes, formerly in views, moved to wrappers.
- Replaced `DownloadView` by `PathDownloadView` and `StorageDownloadView`. Use the right one depending on the use case.

1.0 (2012-12-04)

- Introduced optimizations for Nginx X-Accel: a middleware and a decorator
- Introduced generic views: `DownloadView` and `ObjectDownloadView`
- Initialized project

Notes & references

3.13 Contributing

This document provides guidelines for people who want to contribute to *django-downloadview*.

3.13.1 Create tickets

Please use the [bugtracker](#)²² **before** starting some work:

- check if the bug or feature request has already been filed. It may have been answered too!
- else create a new ticket.
- if you plan to contribute, tell us, so that we are given an opportunity to give feedback as soon as possible.
- Then, in your commit messages, reference the ticket with some `refs #TICKET-ID` syntax.

3.13.2 Use topic branches

- Work in branches.
- Prefix your branch with the ticket ID corresponding to the issue. As an example, if you are working on ticket #23 which is about contribute documentation, name your branch like `23-contribute-doc`.
- If you work in a development branch and want to refresh it with changes from master, please [rebase](#)²³ or [merge-based rebase](#)²⁴, i.e. do not merge master.

3.13.3 Fork, clone

Clone *django-downloadview* repository (adapt to use your own fork):

```
git clone git@github.com:benoitbryon/django-downloadview.git
cd django-downloadview/
```

3.13.4 Usual actions

The *Makefile* is the reference card for usual actions in development environment:

- Install development toolkit with [pip](#)²⁵: `make develop`.
- Run tests with [tox](#)²⁶: `make test`.
- Build documentation: `make documentation`. It builds [Sphinx](#)²⁷ documentation in `var/docs/html/index.html`.
- Release project with [zest.releaser](#)²⁸: `make release`.
- Cleanup local repository: `make clean`, `make distclean` and `make maintainer-clean`.

See also `make help`.

3.13.5 Demo project included

The *demo* included in project's repository is part of the tests and documentation. Maintain it along with code and documentation.

²² <https://github.com/benoitbryon/django-downloadview/issues>

²³ <http://git-scm.com/book/en/Git-Branching-Rebasing>

²⁴ <http://tech.novapost.fr/psycho-rebasing-en.html>

²⁵ <https://pypi.python.org/pypi/pip/>

²⁶ <http://tox.testrun.org>

²⁷ <https://pypi.python.org/pypi/Sphinx/>

²⁸ <https://pypi.python.org/pypi/zest.releaser/>

Notes & references

d

django_downloadview.files, ??
django_downloadview.views.http, ??
django_downloadview.views.object, ??
django_downloadview.views.path, ??
django_downloadview.views.storage, ??
django_downloadview.views.virtual, ??